DARMA®

DARMA
ADHESIVE
Interior Tile Adhesive

OVERVIEW

Darma adhesive is a type of adhesive which is used for internal application to adhere interior wall and floor tiles with good bonding and consistency. It is single component Portland cement based tile adhesive containing cement with selected grades of sand and several additives..

PROPERTIES

- Excellent adhesion to internal surface
- Increase ceramic tiles impact resistance
- Good bonding and consistency
- High workability and durability
- Easy to apply
- High rigidity and strength after hardening
- Resist water penetration

AREAS OF APPLICATION

- Bath rooms
- kitchen
- Interior wall surfaces
- Balconies
- Laundry areas Stone finish

SURFACE PREPARATION

- Clean the surface
- Any adhesion reducing or bond breaking substances like oil, grease, paints, dust , sealers, waxes, must be removed
- Make sure the surface is rigid enough to support the tiles
- The surface should be smooth and level enough to receive the tile
- Dampen the surface without leaving any standing water
- Prepare the position of the tile
- Prepare if there is any tile spacer
- Cut tiles for barriers and corners using corner tile trim

MIXING

- Use 5.5L of water to mix 25kg of Darma Adhesive

APPLICATION

- Apply Darma adhesive on the surface using notched trowel for a minimum uniform thickness of 2mm.
- Press firmly the tile on to the prepared surface for certain seconds to ensure good contact with the adhesive.
- After finishing of the tiling process, grout the surface wall tiles using Darma Filler.

COVERAGE

• It depends on the cleanness and levelness of the surface; A 25kg Darma adhesive covers 5m2 of tiled surface.

PACKAGING

• 25 kg bag

STORAGE

• 24 months; when stored in dry place in unopened and undamaged original packaging.

PRECAUTIONS

• Eyes, nose and skin should be protected by wearing security goggles, gloves and dust mask.
• In case of skin contact, wash with plenty of water.
• In case of eye contact, rinse cautiously with water for several minutes. Seek medical advice if the irritation continues.

Technical data

Appearance	Powder
Color	Grey

CERTIFIED COMPANY
ISO 9001:2015

GRACE CONSTRUCTION CHEMICALS

+251 964 234 444
+251 929 337 886
@grace_construction_chemicals